

LEAK-TITE® BLUE THREAD SEALANT WITH PTFE RESINS



FEATURES:

- Formulated for new thin wall threaded pipe.
- Contains PTFE Resin particles for greater sealing power.
- Will not harden or dry out over time. Remains flexible for easy disassembly.
- Non-toxic, contains no solvents.
- Sticks to hot, oily threads.
- Ideal for use on production lines and in fabrication shops.
- Easy clean up, will not stain hands or clothing.
- Sealing Temperature Range: -50° to 500°F (-45° to 260° C).
- Working Pressure: 5,000 PSI for liquids, 1,500 PSI for gases.

TYPICAL APPLICATIONS:

- Seals all types of pipe threads: Steel, Brass, Iron, and PVC, ABS, CPVC Plastic.
- Recommended Services: Water, Steam, Air, Natural Gas, Refrigerants and Ammonia. Contact factory for specific use recommendations. **NOT RECOMMENDED FOR USE WITH OXYGEN SERVICE.**

RECOMMENDED INDUSTRIES:

- Fire Sprinkler Piping
- Plumbing
- Air Conditioning/Refrigeration
- Chemical Processing Plants
- Commercial/Residential Building Maintenance

ORDERING INFORMATION

PART NO.	SIZE	QTY /CASE	WT./CASE
46009	¼ pt. BIC	24	13
46019	½ pt. BIC	24	22
46029	1 pt. BIC	24	43
46013	1 qt.	12	42
46049	1 qt. BIC	12	40
46014	1 gal.	4	53
46015	5 gal.	1	65
40669	55 gal.	1	700

BIC = Brush-in-Cap

CALL OR WRITE FOR MORE INFORMATION.

LA-CO INDUSTRIES, INC./MARKAL COMPANY
1201 Pratt Blvd., Elk Grove Village, IL 60007-5746
(847) 956-7600 FAX: (847) 956-9885
Customer Service Line: (847) 956-3867

Visit our website at: www.laco.com